

## Certificate of Conformity

Certificate Number: CN-PV-210111

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specifications /standards at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant Name & Address: Shenzhen SOFARSOLAR Co., Ltd.

401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community,

XinAn Street, BaoAn District, Shenzhen, China

Product Description: Anti-backflow system

Ratings & Principle See Annex to Certificate of Conformity

Characteristics: Models/Type References:

SOFAR 3.3KTLX-G3, SOFAR 4.4KTLX-G3, SOFAR 5KTLX-G3-A SOFAR 5.5KTLX-G3, SOFAR 6.6KTLX-G3, SOFAR 8.8KTLX-G3, SOFAR 11KTLX-G3, SOFAR 10KTLX-G3-A

SOFAR 11KTLX-G3-A, SOFAR 12KTLX-G3

Brand Name: 5 FAR

Specification/Standard: UNE 217001 IN: October 2020

Tests for systems that avoid the discharge of energy to the distribution

network

Certificate Issuing Office Intertek Testing Services Ltd. Shanghai

Name & Address: West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free

Trade Zone, Shanghai, P. R. China

Test Report Number: 210416108GZU-015

(suste

Additional information in Appendix.

Signature

**Certification Manager: Grady Ye** 

Date: 17 May 2021



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

MODEL	SOFAR 3.3KTLX- G3	SOFAR 4.4KTLX- G3	SOFAR 5KTLX- G3-A	SOFAR 5.5KTLX- G3		
Max PV voltage	1100Vdc					
MPPT Voltage range	140-1000Vdc					
Max. input current	15/15A					
PV Isc	22.5/22.5A					
Rated power(W)	3000	4000	5000	5000		
Max.apparent power (VA)	3300	4400	5000	5500		
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A		
Output voltage	3W/N/PE 230Vac/400Vac					
Nominal Frequency	50 Hz					
Power Factor	1 default (adjustable+/-0.8)					
Ambient Temperature	-30℃ - +60℃					
Protection Degree	IP65					
Protection Class	Class I					
Software Version	V000001					



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

SOFAR 6.6KTLX- G3	SOFAR 8.8KTLX- G3	SOFAR 8.8KTLX- G3-A	SOFAR 10KTLX- G3-A		
1100Vdc					
140-1000Vdc					
15/15A		15/30A			
22.5/22.5A		22.5A/45A			
6000	8000	8000	10000		
6600	8800	8800	10000		
3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A		
3W/N/PE 230Vac/400Vac					
50 Hz					
1 default (adjustable+/-0.8)					
-30℃ - +60℃					
IP65					
Class I					
V000001					
	G3 15/ 22.5/ 6000 6600	G3 G3  1100 140-10 15/15A  22.5/22.5A  6000 8000 6600 8800 3×10.0 A 3×13.3 A 3W/N/PE 23  50 1 default (adj -30°C -	G3 G3 G3-A  1100Vdc  140-1000Vdc  15/15A 15/  22.5/22.5A 22.5A  6000 8000 8000 6600 8800 8800 3×10.0 A 3×13.3 A 3×13.3 A  3W/N/PE 230Vac/400Vac  50 Hz  1 default (adjustable+/-0.8)  -30°C - +60°C  IP65  Class I		



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-210111

MODEL	SOFAR 11KTLX-G3	SOFAR 11KTLX-G3-A	SOFAR 12KTLX-G3		
Max PV voltage	1100Vdc				
MPPT Voltage range	140-1000Vdc				
Max. input current	15A/15A	15A/30A			
PV Isc	22.5/22.5A	22.5A/45A			
Rated power(W)	10000	10000	12000		
Max.apparent power (VA)	11000	11000	13200		
Max output current	3×16.7 A	3×16.7 A	3×20.0 A		
Output voltage	3W/N/PE 230Vac/400Vac				
Nominal Frequency		50 Hz	0		
Power Factor	1 default (adjustable+/-0.8)				
Ambient Temperature	-30℃ - +60℃				
Protection Degree	IP65				
Protection Class	Class I				
Software Version	V000001				